

✓ **CAT6A S/FTP Data Patch Cord 500Mhz 10Gbps LSZH**



Ethernet Mesafe Uzaticilar & IP Kamera Cözümleri

Teknik Özellikler

- 500Mhz Band Genişliđi
- PIMF (Perler Metal Folyo içinde)
- Tam Bakır 4*2*26AWG
- LSZH (Low Smoke Zero Halogen)
- RJ45 Shielded Konnektör
- RJ45 Tırnak Korumalı

Uygulama Alanları

- 10GBASE-T Ethernet
- 100BASE-TX Fast Ethernet
- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet
- 10BASE-TX Ethernet

Empedans	64kHz 1~250MHz	125Ω ± 20%		
	Frekans (Mhz)	Insertion Loss (dB)	Next (dB)	PS NEXT (dB)
Zayıflama				
&	100MHz	28.62	44.4	42.4
NEXT	250MHz	46.62	38.4	36.4
&	300MHz	51.42	37.2	35.2
PS NEXT	400MHz	60.12	35.4	33.4
	500MHz	67.92	33.9	31.9

0212 912 43 49 & bayi@gelecekbtt.com

www.gelecekbtt.com

www.switchmerkezi.com

www.gbicmodul.com

www.clrnetworks.com

www.netkablo.com