



TYPE:
 1. RJ45 CAT7 SHIELDED TOOLLESS PLUG
 2. COLOUR: WHITE

CABLE MATCHED:
 1. SOILD AND STRANDED
 2. 22AWG/23AWG/24AWG

ELECTRICAL:
 1. CONTACT RESISTANCE: 20m OHM
 2. INSULATION RESISTANCE: $\leq 500M$ OHM @100 V DC
 3. WITHSTAND VOLTAGE: DC1000V AC700V RMS 60HZ. 1MIN
 4. CAT7 PERMANENT LINK: CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:
 1. STORAGE: -40° / $+70^{\circ}$
 2. OPERATION: -10° / $+60^{\circ}$

MECHANICAL:
 1. PLASTIC MATERIAL: NEW PC
 2. SHIELDED MATERIAL: ZINC ALLOY NICKEL PLATING
 3. TERMINAL PINS: PHOSPHOR BRONZE, ZIN PLATING
 4. RJ45 CONTACT LIFE: 750 TIMES MIN
 5. IDC TERMINAL LIFE: 250 TIMES MIN



Logo length: 8mm



ONET

Optical Communications

Material	Item No.			ON-221021
Angles Projection	Scale	Unit	Part Name	
	A4	X:1	STP Cat.7 Modular Plug	
Sheet	1 OF 1	Version: A/0	ERP	Part No.