



Product Features

1. Professional WHDI (MIMO/OFDM) technology
2. Uncompressed 3G/HD/SD-SDI and HDMI
3. Support full-hd 1080P/60Hz video display with very low latency
4. 150m (LOS) transmission distance (max 200m)
5. 5.1-5.9GHz license-free operation frequency
6. New OLED screen, faster FM and more intuitive display parameter
7. Multicast – 1 transmitter to multi receivers
8. AES-128 encryption transmission
9. All-metal housing, durable
10. Pure hardware connection, Plug and Play
11. Support external Li-battery supply for mobile convenience
12. Support Hot-shoe installation with 1/4 screw nut
13. Wide voltage design, support DC7V-36V voltage

Specification

Model NO.	CLR-WHD-151	
	Transmitter	Receiver
Input	3G/HD/SD-SDI × 1 HDMI × 1	/
Output	/	3G/HD/SD-SDI × 1 HDMI × 1
SDI Format	480i (59.94) 720p (60/59.94/50) 1080i (60/59.94/50) 1080p (60/59.94/50/30/29.97/25/24/23.98) 3G, HD and SD-SDI (auto-selected) SMPTE-259/274/292/296/372/424/425	
HDMI Format	525i/625i 720p (50/59.94/60) 1080i (50/59.94/60) 1080p (60/59.94/50/30/29.97/25/24/23.98)	
Input Audio Format	SDI embedded 4 channel 24 bit/48KHz	/
Output Audio Format		SDI embedded 4 channel 24 bit/48KHz
Signal Indicator	Link-Yellow; VIDEO-Green	Link-Yellow; Wireless RSSI-Blue (5 LEDs); VIDEO-Green
Transmission Power	Maximum 15dBm	/
Receiver Sensitivity	/	-75dBm
Frequency Band	5.1-5.9GHz, configurable with China, North American, Europe, etc	
Modulation Mode	OFDM 16QAM	
Transmission Distance	150m (MAX 200)	
Latency	≤1ms	
Occupied Bandwidth	20/40MHz	
Install Way	1/4"-20 Thread Socket	
Working Temperature	0 ~ 40°C	
Storage Temperature	-20~60°C	
Power Connector	4-PIN LEMO DC	
Input Voltage	DC 7-36V	
Power Consumption	<6.5W	<6W
Unit Size	122.2Lx67Hx25.3Dmm (don't include antennas)	152.2x95.4x26mm (don't include antennas)
Unit Weight	270g	400g