


# CS82U/CS84U

## 2/4-Port PS/2-USB KVM Switch


The CS82U / CS84U PS/2-USB KVM Switch is a desktop control unit that allows users to access two or four computers from a single KVM console (PS/2 or USB keyboard and mouse, and VGA monitor). In addition, CS82U / CS84U comes with ATEN's new Video DynaSync™ technology, which eliminates boot-up display problems and optimizes resolution.

Setup is fast and easy; simply plug cables into their appropriate ports. There is no software to configure, no installation routines, and no incompatibility problems. Since the CS82U / CS84U intercepts keyboard input directly, it will work on multiple computing platforms.

CubiQ™



### Setup



### Features

- One PS/2-USB VGA console controls two (CS82U) or four (CS84U) VGA interface computers.
  - **Dual Interface** – supports computers with PS/2 or USB keyboards and mice
  - **Computer selection via front panel pushbuttons, hotkeys, and mouse**
  - Multiplatform support – Windows, Linux, Mac, and Sun
  - Superior video quality – 2048 x 1536; DDC2B
  - **Video DynaSync™** – Exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
  - **Console port emulation/bypass feature supports most mouse drivers and multifunction mice**
  - Complete keyboard emulation for error-free booting
  - Mac/Sun keyboard support and emulation\*
  - **Multilingual keyboard mapping** – supports English, Japanese, and French keyboards
  - **Gaming keyboard support**
  - Auto Scan Mode for monitoring all computers
  - Firmware upgradable
  - Non-powered
- \* 1. PC keyboard combinations emulate Mac/Sun keyboards  
2. Mac/Sun keyboard work only with their own computers

### Specifications

Function		CS82U	CS84U
Computer Connections		2	4
Port Selection		Front Panel Pushbuttons; Hotkey, USB Mouse	
Connectors	Console Ports	Keyboard 1 x USB Type A Female (Black), 1 x 6-pin Mini-DIN Female (Purple)	Keyboard 1 x USB Type A Female (Black), 1 x 6-pin Mini-DIN Female (Purple)
	Video	1 x HDB-15 Female (Blue)	1 x HDB-15 Female (Blue)
	Mouse	1 x USB Type A Female (Black), 1 x 6-pin Mini-DIN Female (Green)	1 x USB Type A Female (Black), 1 x 6-pin Mini-DIN Female (Green)
	KVM Ports	2 x SPHD-18 Female (Yellow)	4 x SPHD-18 Female (Yellow)
Power		1 x DC Jack	1 x DC Jack
Switches	Selected	2 x Pushbutton	4 x Pushbutton
LEDs	On Line	2 (Orange)	4 (Orange)
	Selected	2 (Green)	4 (Green)
Emulation	Keyboard / Mouse	PS/2, USB	
Video		2048 x 1536 @ 60 Hz; DDC2B	
Scan Interval		3, 5, 10, 20 secs. (5 secs. default)	
Power Consumption		DC 5V, 1.1W	DC 5V, 1.2W
Environment	Operating Temp.	0–50°C	
	Storage Temp.	–20–60°C	
	Humidity	0–80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	0.54 kg	0.77 kg
	Dimensions (L x W x H)	14.00 x 8.70 x 5.50 cm	21.00 x 8.70 x 5.50 cm

\* Product specifications and appearance are subject to change without notice.