


# Excel Category 6A Cable U/FTP S-Foil LS0H Dca 500m Reel - Ice Blue

Item Code: 100-191

**excel**  
without compromise.



✕ Individual foil pairs with overall braid screen

✕ Category 6A Performance to 1000 MHz

✕ Sequential metre markings

✕ Euroclass Dca-s2-d2-a1

## Product Overview

Excel Category 6A Screened S/FTP Cable is designed and manufactured to meet and exceed the ISO, CENELEC and TIA standards. This delivers Class FA link and channel performance supporting all applications detailed and proposed within the standards. This superior performance cable is Delta Component Verified.

Each cable consists of 4 pairs individually wrapped in a covering of high quality, strong, aluminium/polyester foil tape providing an individual screen for each pair. These sub units are then cabled together, with the pairs set to different lay lengths to ensure optimum performance, an overall braid screen is applied to provide further immunity to outside noise and to mitigate any risk of alien cross talk.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

## Product Specifications

Feature	Values
Category	6A (IEC)
Overall screening	None
Conductor screening	Foil
Outer sheath colour	Ice Blue
Reaction-to-fire class according to EN 13501-6	Dca
Smoke development class according to EN 13501-6	s2
Euro class flaming droplets/particles according to EN 13501-6	d2
Euro class acidity according to EN 13501-6	a1
AWG-size	23


# Excel Category 6A Cable U/FTP S-Foil LS0H Dca 500m Reel - Ice Blue

Item Code: 100-191

**excel**  
without compromise.

Specification core insulation	PE
Core identification	Colour
Outer sheath material	Copolymer
Flame retardant	In accordance with EN 60332-1-2 and EN 50399
Outer diameter approx.	6.7 mm
Installation Temperature Range	0...60 °C
Operating Temperature Range	-20...60 °C
NVP value	76 %
Conductor category	Class 1 = solid
Total number of cores	8
Stranding element	Pairs
Conductor surface	Bare

## Cross-section diagram



## Cable specifications

Features	Values
Dielectric strength	1200 V dc or 850 V ac
Maximum Pulling Load	60N/6.1KgF
MBR during installation	8x cable OD
MBR installed	4x cable OD

## Standards

Applicable standard	Subject
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
EN 50173-1:2011	Information technology. Generic cabling systems - General requirements
EN 50173-2:2007 + A1:2010	Information technology. Generic cabling systems - Office premises
BS EN 50288-6-1:2013	Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2011	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions - Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
RoHS	Restriction of Hazardous Substances - Compliant

# Excel Category 6A Cable U/FTP S-Foil LS0H Dca 500m Reel - Ice Blue

Item Code: 100-191



## Part Number Table

Part Number	Description
100-191	Excel Category 6A Cable U/FTP S-Foil LS0H Dca 500m Reel - Ice Blue
100-191-305M	Excel Category 6A Cable U/FTP S-Foil Dca LS0H 305m Box - Ice Blue
100-191-BK	Excel Category 6A Cable U/FTP S-Foil LS0H Dca 500m Reel - Black
100-191-WT-305M	Excel Category 6A Cable U/FTP S-Foil Dca LS0H 305m Box - White
100-194	Excel Category 6A Dual Cable U/FTP S-Foil Dca LS0H 500m Reel - Ice Blue
100-198	Excel Category 6A Cable U/FTP S-Foil Dca LS0H 500m Reel - White
170-191	Excel Category 6A Cable U/FTP S-Foil Cca LS0H 500m Reel - Ice Blue
170-191-305M	Excel Category 6A Cable U/FTP S-Foil Cca LS0H 305m Box - Ice Blue
170-191-WT-305M	Excel Category 6A Cable U/FTP S-Foil Cca LS0H 305m Box - White
170-194	Excel Category 6A Dual Cable U/FTP S-Foil Cca LS0H 500m Reel - Ice Blue
170-198	Excel Category 6A Cable U/FTP S-Foil Cca LS0H 500m Reel - White
190-191	Excel Category 6A Cable U/FTP S-Foil B2ca LS0H 500m Reel - Ice Blue
190-191-305M	Excel Category 6A Cable U/FTP S-Foil B2ca LS0H 305m Box - Ice Blue
190-191-WT-305M	Excel Category 6A Cable U/FTP S-Foil B2ca LS0H 305m Box - White
190-198	Excel Category 6A Cable U/FTP S-Foil B2ca LS0H 500m Reel - White

Excel is a world class premium performing end to end infrastructure solution designed,  
Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.